

# liftrroller® wall

## TECHNICAL SPECIFICATIONS

	Available models		
	Narrow	Standard	Extended
Minimum window width *	900mm	1200 mm	1200 mm
Maximum width loading area**	990mm	1550 mm	1550 mm
Maximum wall thickness	500mm	500mm	800mm
Minimum ceiling height	2150 mm	2150 mm	2950mm
Maximum ceiling height	3900 mm	3900mm	L1700 mm
Minimum height roller table	930mm	930mm	930mm
Maximum height roller table	1225 mm	1225 mm	1225 mm
Maximum parapet height	1050 mm	1050 mm	1050 mm
Tare weight total***	177 kg	187 kg	197 kg
Max. load capacity (WLL)	1200 kg	1200 kg	1200 kg

### Do you need other sizes?

Parts from each of the models can be combined to fit your needs. We also have customized versions. Contact your local Liftrroller Dealer

\* Adjustable width to fit window size.

\*\* Fully extended width between the wires.

\*\*\* Easily disassembled into manageable parts, no tools needed. (For windows wider than 1700 mm. contact your local

Liftrroller Dealer for advice on how make on site adaptations.)



**liftrroller.**

**AUSTRALIAN Distributor**

**support@liftrroller.com.au**

**1300 222 300**

**3/41 Smith Street, Hillsdale, 2036, New South Wales, Australia**

Faster, Easier, Safer